# NewLook® International, Inc. TiqueWash™ Technical Information Sheet



NewLook International, Inc. **TiqueWash** is a superior antiquing colorant used to easily create a natural, multi-toned finish on textured concrete surfaces. The high-quality water based formula includes ultra-fine polymers for improved surface penetration and strong adhesion when sealed with NewLook SmartSeal™ or other compatible sealers. The TiqueWash powder is mixed with water to create a translucent color wash that, once applied, runs off high spots and settles in the low areas of relief of textured concrete. Use TiqueWash to restore the color of weathered concrete or create an antique color finish for stamped surfaces.

### **USES & BENEFITS**

- Restore the color of weathered concrete
- Create an antique (two-toned) color finish on stamped concrete surfaces
- Strong bond when sealed with NewLook SmartSeal AU, SmartSeal WB, or other compatible sealers
- Low hazing properties
- Fade resistant pigmentation resists UV damage

#### **INSTRUCTIONS**

Thoroughly clean the concrete surface before applying TiqueWash. Remove existing sealer and other foreign materials using NewLook EasyStrip™ and NewLook Concrete Degreaser™. New concrete may need to slightly etched using NewLook EcoAcid™ to achieve desired porosity.

Using the included measuring cup, mix into a separate bucket one to three scoops of TiqueWash powder (depending on desired color intensity) with one gallon of clean water. On average, one scoop is sufficient. Pre-moisten the surface with water to help ensure color consistency and proper settling of the pigments. Spread mixed TiqueWash across the surface with a NewLook Applicator Brush™ or clean, soft push broom. Apply a liberal and uniform amount of material. Keep the product mixture agitated throughout the installation process to ensure color consistency and prevent pigment from settling. Clean up with water.

# **COVERAGE**

One three (3) pound container covers approximately 200–300 square meters

# **STORAGE**

Store unmixed TiqueWash in a cool, dry place (in temperatures below 48° C). Shelf life is approximately two (2) years when containers are kept tightly sealed.

# LIMITED PRODUCT WARRANTY

This product is warranted to be of uniform quality within manufacturer's tolerances. NewLook International, Inc. has no control over the use of TiqueWash ("Product"), therefore no other oral or written representation or statement of any kind, express or implied, now or hereafter made is authorized or warranted by NewLook or its affiliates, and NewLook and its affiliates hereby disclaims all such warranties. The end user shall be responsible for determining Product suitability, including surface conditions and climate conditions, and end user assumes all risks and liability. NewLook shall not be liable for special, incidental, or consequential damages, including delays or lost profits. Communication of this warranty and its limitations to end users is not the responsibility of NewLook but should be communicated by those in direct contact with the end user. Any claim regarding product defect must be received in writing within one year from the date of manufacture. No claim will be considered without such written notice or after the specified time interval. Product is intended to be used by licensed contractors and installers, experienced and trained in the use of Product. Please use common sense.

**CAUTION:** KEEP AWAY FROM CHILDREN. Do not inhale or ingest. WARNING: This product may contain a chemical known to the state of California to cause birth defects or other reproductive harm.